

WHAT IS CLAIMED IS:

1. A treatment device, comprising:

a housing in which an electric component including a power  
5 supply is incorporated;

a contact projected provided on said housing and used with  
a tip portion being contacted with a skin surface of an object to  
be treated;

a waterproofing sealing member which seals an accommodating  
10 portion for the electric component in said housing against the  
outside; and

a contact drive mechanism which reciprocates said contact  
the tip portion of which is contacted with the skin surface of the  
object to be treated in a direction along the skin surface.

15 2. The treatment device as set forth in claim 1,  
wherein first and second contact groups respectively by  
providing a plurality of said contacts, and

wherein the contact drive mechanism reciprocates said first  
and second contact groups respectively in a manner that approach  
20 or separation of a tip part of said first contact group and a tip  
part of the second contact group is repeated.

3. The treatment device as set forth in claim 2,  
wherein, in the first and second contact groups, the plural  
contacts of the first contact group and the plural contacts of the  
25 second contact group are arranged zigzag to evade intersection of  
movement trajectories of the contacts.

4. The treatment device as set forth in claim 1,  
wherein the housing is constituted with a first casing having

the accommodating portion for the electric component and a second casing supporting said contact, and

wherein an attachment/detachment mechanism to join the second casing in relation to the first casing attachably/detachably is provided.

5        5. The treatment device as set forth in claim 1,  
wherein the contact is a brush.

6. The treatment device as set forth in claim 1, further comprising:

10        a light irradiation mechanism which irradiates light of a certain wavelength region to the skin surface of the object to be treated.

7. The treatment device as set forth in claim 1,  
wherein the contact is formed of a translucent material.

15        8. A treatment device, comprising:

a light irradiation mechanism which irradiates light of a certain wavelength region to a skin surface of an object to be treated;

a housing in which the light irradiation mechanism and an electric component including at least a power supply are incorporated;

20        a waterproofing sealing member which seals an accommodating portion for the electric component in said housing against the outside;

first and second brush groups made by making a plurality of brushes projected on said housing into units, the brushes having  
25        translucency transmitting the light emitted by said light irradiation mechanism and being used with tip portions contacted with the skin surface of the object to be treated; and

a brush drive mechanism which reciprocates the first and second

brush groups respectively in a direction along the skin surface in a manner that approach or separation of a tip part of the first brush group and a tip part of said second brush group tip portions of which are contacted with the skin surface of the object to be treated is repeated.

5       9.   The treatment device as set forth in claim 8,  
          wherein, in the first and second brush groups, the plural brushes of the first brush group and the plural brushes of the second brush group are arranged zigzag to evade intersection of movement  
10   trajectories of the brushes.

          10.   The treatment device as set forth in claim 8,  
          wherein the housing is constituted with a first casing having the accommodating portion for the electric component and a second casing supporting the respective brushes, and  
15       wherein an attachment/detachment mechanism to join the second casing in relation to the first casing attachably/detachably is provided.